

lammina

12AL SUPERLIGHT

Aluminum Tenders



Overal Length	: 12'/ 3.66m	Number of Chambers :	3	Maximum HP	: 30hp / 22.4kw
Overal Beam	: 6′1″/ 1.85m	Person Capacity :	6	Shaft Length	: 20" / 50.8cm
Inside Length	: 8'10"/ 2.70m	Weight :	198lb / 90kg	RDC Design Category	: C
Inside Beam	: 2'11"/ 0.89m	Weight with Bow Locker:	213lb/97kg		
Tube Diameter	: 18"/ 0.46m	Recommended HP :	25hp /18.7kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings

- Deck Drain with Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Single Solid Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Maintenance Kit
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Stern Seat
- Paddles with Aluminum Shaft

- Owner's Manual
- 3 Layer Reinforced SeamsRubber Protector on Full Length of Keel

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat

- Fiberglass Console
- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit

