



lammina | **9UL** | **Ultra Light Aluminum Tenders**



| | | | |
|------------------|-------------------------------|----------------------------|-----------------------------|
| S P E C S | Overall Length : 9'1" / 2.76m | Number of Chambers : 2 | Shaft Length : 15" / 38.1cm |
| | Overall Beam : 4'11" / 1.50m | Person Capacity : 4 | RDC Design Category : C |
| | Inside Length : 6'3" / 1.90m | Weight : 75lb / 34kg | |
| | Inside Beam : 2'3" / 0.70m | Recommended HP : 8hp / 6kw | |
| | Tube Diameter : 16" / 0.41m | Maximum HP : 10hp / 7.5kw | |

| | | | |
|--|--|--|--|
| S T A N D A R D F E A T U R E S | <ul style="list-style-type: none"> ■ Shallow "V" Marine Grade Aluminum Hull ■ Non-Skid Rubber Floor Panels ■ Plastic External Transom Plate ■ Aluminum Internal Transom Plate With Security Lip ■ Aluminum Bow Eye ■ 3 Aluminum Davit Lifting Points ■ Aluminum Bow Towing Rings ■ Deck Drain with Plug ■ Orca (CSM) Five Layer Coated Fabric | <ul style="list-style-type: none"> ■ Raised Single Rub Rail ■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves ■ 1 Front & Side Orca (CSM) Fabric Handles on Tubes ■ 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes ■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes ■ Removable Rowing Seat ■ Oarlock Bases ■ Telescopic Oars with Aluminum Shaft | <ul style="list-style-type: none"> ■ Paddle Holders ■ Hand Pump ■ Maintenance Kit ■ Owner's Manual ■ 3 Layer Reinforced Seams |
|--|--|--|--|

| | |
|--|---|
| O P T I O N A L F E A T U R E S | <ul style="list-style-type: none"> ■ Tube Chaps ■ Boat Cover ■ Chock Set |
|--|---|

