

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXSEAL C1617-Protective Primer 161Conv farblos / transparent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Industrial serial painting

1.3 Details of the supplier of the safety data sheet

Producer : Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:

Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone : +49 (0) 40 75103 0
Telefax : +49 (0) 40 75103 375
E-mail address of person responsible for the SDS : sdb_info@umco.de

1.4 Emergency telephone number

Emergency telephone number : +44 1865 407333 (NCEC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated	H373: May cause damage to organs through pro-

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank Postbank	Hamburg	59273300	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
	Hamburg	373205	200 100 20	PBNKDE33HAN	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau
Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

exposure, Category 2

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear, 4,4'-isopropylidenediphenol-1-chloro-2,3-epoxypropane co-oligomer and triethylenetetramine
xylene
butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	59273300	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PNKDEFF200	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Bureau Veritas Certification: ISO 9001, TS 16949, EN 9100
Personlich haftende Gesellschafterin: Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Hardener based on polyamine / amino adduct

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear, 4,4'-isopropylidenediphenol-1-chloro-2,3-epoxypropane co-oligomer and triethylenetetramine	157707-71-6 500-380-2	Eye Dam. 1; H318	>= 40 - <= 100
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 25 - < 40
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 10 - < 12.5

For explanation of abbreviations see section 16.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	59273300	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PBNKDE33HAN	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO
ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform
appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent
materials, e.g. sand, earth, vermiculite, diatomaceous earth
and place in container for disposal according to local regula-
tions (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with the skin and the eyes.
Prevent the creation of flammable or explosive concentrations
of vapour in air and avoid vapour concentrations higher than
the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the ap-
plication area.

Advice on protection against fire and explosion : The product should only be used in areas from which all na-
ked lights and other sources of ignition have been excluded.
Preparation may charge electrostatically: always use earthing
leads when transferring from one container to another. Opera-
tors should wear anti-static footwear and clothing. No sparking
tools should be used. Vapours are heavier than air and may
spread along floors. Vapours may form explosive mixtures
with air.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 220 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 441 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will		



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

lead to systemic toxicity.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value	
xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³	
	Workers	Dermal	Long-term systemic effects	212 mg/kg bw/day	
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m ³	
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day	
	Consumers	Oral	Long-term systemic effects	12.5 mg/kg bw/day	
	butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m ³
Consumers		Inhalation	Long-term systemic effects	55.357 mg/m ³	
Consumers		Dermal	Long-term systemic effects	3.125 mg/kg bw/day	
	Consumers	Oral	Long-term systemic effects	1.562 mg/kg bw/day	
	xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
		Workers	Dermal	Long-term systemic effects	212 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	65.3 mg/m ³	
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day	
	Consumers	Oral	Long-term systemic effects	12.5 mg/kg bw/day	
	butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m ³
Consumers		Inhalation	Long-term systemic effects	55.357 mg/m ³	
Consumers		Dermal	Long-term systemic effects	3.125 mg/kg bw/day	
	Consumers	Oral	Long-term systemic effects	1.562 mg/kg bw/day	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Soil	2.31 mg/kg dry weight (d.w.)
butan-1-ol	Fresh water	0.082 mg/l
	Marine water	0.008 mg/l
	Fresh water sediment	0.324 mg/kg dry weight (d.w.)
	Marine sediment	0.032 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Soil	0.017 mg/kg dry weight (d.w.)
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Soil	2.31 mg/kg dry weight (d.w.)
butan-1-ol	Fresh water	0.082 mg/l
	Marine water	0.008 mg/l
	Fresh water sediment	0.324 mg/kg dry weight (d.w.)
	Marine sediment	0.032 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Soil	0.017 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

- Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.
- Respiratory protection : If the solvent concentration is above the air limit values, a breathing apparatus approved for this purpose must be worn. Use half-mask model with cartridge or air-fed.
- Protective measures : Do not eat or drink during work - no smoking. Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : according product name
- Odour : characteristic
- Upper explosion limit : 10.0 %(V)
- Lower explosion limit : 1.0 %(V)
- Flash point : 27 °C
Method: ISO 13736
- Auto-ignition temperature : > 400 °C
- pH : 7 - 9 (20 °C)
Concentration: 10 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

Viscosity
Viscosity, kinematic : > 21 mm²s

Flow time : 30 s
Cross section: 4 mm
Method: DIN 53211

21 s
Cross section: 6 mm
Method: ISO 2431

Solubility(ies)
Water solubility : insoluble

Vapour pressure : ca. 100 hPa (50 °C)

Density : ca. 0.95 g/cm³ (20 °C)

9.2 Other information

Miscibility with water : immiscible

Solvent separation : < 3 % (V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation
as defined by dangerous goods regulations.

Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.
Corrosive effect of product in contact with skin, eyes and mucous membranes.
Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 40 %, 380 g/l

Other regulations:

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN30	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	59273300	200 300 00	HYVEDE33HAN30	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PBNKDE33HAN30	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Büro/Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100
Michael O. Grau
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 1556000000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

- H312 : Harmful in contact with skin.
- H315 : Causes skin irritation.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H373 : May cause damage to organs through prolonged or repeated exposure.
- H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Asp. Tox. : Aspiration hazard
- Eye Dam. : Serious eye damage
- Eye Irrit. : Eye irritation
- Flam. Liq. : Flammable liquids
- Skin Irrit. : Skin irritation
- STOT RE : Specific target organ toxicity - repeated exposure
- STOT SE : Specific target organ toxicity - single exposure
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- GB EH40 BAT : UK. Biological monitoring guidance values
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative)

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	59273300	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PBNKDE33HAN	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Bureau Veritas Certification: ISO 9001, TS 16949, EN 9100
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXSEAL C1617-Protective Primer
161Conv
Quality No.: 155600000000

Revision Date 28.02.2023
Print Date 28.02.2023
Version 3

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN