


SWA6 COMBINED BLUETOOTH STEREO SUBWOOFER



Connect smartphones and MP3 players to the subwoofer via Bluetooth or RCA inputs



Built-in 288W amplifier powers the internal subwoofer and external speakers



Connect up to four speakers (sold separately)

Halo Aerial Technology provides unrivalled Bluetooth range and signal strength

Tuned port for outstanding subwoofer performance

Electronic Crossover automatically balances speaker and subwoofer for optimum performance

KEY FEATURES

Bluetooth® **Bluetooth Audio** Easily stream your favorite tunes direct from your smartphone to the SWA6 with Bluetooth Audio support.

HALO AERIAL TECHNOLOGY **Halo Aerial Technology** Receive a stronger Bluetooth signal and greater range in all directions over standard Bluetooth with Halo Aerial Technology.

TUNEDPORT **Tuned Port** provides outstanding subwoofer performance, showcasing your favorite music in all its sonic glory.

Remote Ready Connect wired or wireless remote controls for an easier listening experience with the ability view track info and control your SWA6's features.

USB CHARGING **USB Charging** Connect your smartphone via the USB cable to charge your smartphone or USB device.



Electronic Crossover Automatically balanced speaker and subwoofer outputs for no-hassle perfect sound quality across all frequencies.



288W Amplifier Built-in 288W Amplifier powers both the internal subwoofer and up to four external speakers (sold separately).



AUX Connect devices via stereo RCA cable with variable input gain of 400mv, 2V or 4V available for optimum performance with all devices.



2 Year Warranty Aquatic AV products are built to be reliable and durable. The SWA6 comes with a two year warranty that can be extended with product registration.

SPECIFICATIONS

Type:	Bluetooth Ready Active Subwoofer with full range speaker output
Subwoofer Cone Size:	8"
Subwoofer Frequency Response:	26 - 125 Hz
Impedance:	4 Ohm & 2 Ohm stable
Sensitivity:	86dB
Power (max):	288W
Waterproof:	IPx4
Chassis Material:	ABS
Cone Material:	Polypropylene
Inputs:	Bluetooth
	2x RCA with variable 400mv, 2V or 4V input for optimum performance with all devices
Outputs:	2 channel full range output
Device Charging:	Yes - via 3ft USB cable
Frequency Response (amp):	125 - 20,000 Hz
Amplifier Power (max):	72W x 2 (@ 2 Ohms) / 45W x 2 (@4 Ohms)
Certification:	RoHS
Dimensions:	368.3 x 279.4 x 144.2 mm
Additional Features:	Tuned port
	Pre-balanced electronic cross-over
Accessories:	RF6 KIT Wireless Remote Control (sold separately)
	WR6 Wired Remote Control (sold separately)

DIMENSIONS

