

Water-Resistant Contura Switches

Specifically manufactured for use in Blue Sea Systems
Contura Water-Resistant Panels



7929
Contura II



8230
Contura III



8282
Contura III

Use of non Blue Sea Systems Contura Switches will not maintain the water resistant ingress protection rating of Blue Sea Systems panels.

- Vibration, shock, thermoshock, moisture and salt spray resistant
- Mounts in Blue Sea Systems Contura Water Resistant Panels and Contura Switch Mounting Panels

Amperage Max. Operating	20A @ 12V DC, 15A @ 24V DC
Amperage Operating Current	18 Milliamps
Lighted	LED rated 100,000 hours half-life
Seals	Internal and external gasket panel seal
Temperature Rating	-40°C (-40°F) to 85°C (185°F)
Mounting Hole	1.45 in x 0.83 in (36.83 mm x 21.08 mm)
Regulatory	CE marked, meets UL 1500 and ISO 8846 external ignition protection requirements

**IGNITION
PROTECTED**

() = Momentary

Part # Contura II Black	Part # Contura III Gray	Part # Contura III Black	Actuator Position to Light LED	Pole Throw	Action	LEDs
7929	8230	8282	ON	SPST	OFF-ON	1
7930	8231	8292	--	SPST	OFF-(ON)	0
7931	8232	8283	ON	SPDT	ON-OFF-ON	2
7932	8233	8284	ON	SPDT	(ON)-OFF-ON	1
7933	8234	8285	--	SPDT	(ON)-OFF-(ON)	0
7943	7944	7945	(ON)	SPDT	(ON)-OFF-ON	1
7934	8218	8287	ON	DPST	OFF-ON	1
7935	8219	8288	--	DPST	OFF-(ON)	0
7936	8220	8286	ON	DPDT	ON-OFF-ON	2