

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

**SECTION 1: PRODUCT IDENTIFICATION**

<b>Material name</b>	<b>Triple Guard Grease</b>
<b>Product Code</b>	<b>72930</b>
<b>Version #</b>	<b>1.0</b>
<b>Revision date</b>	<b>01-23-2012</b>

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Components</b>	<b>CAS #</b>	<b>Percent</b>
Distillates (petroleum), Hydrotreated Heavy Naphthenic	64742-52-5	0 - 90
Distillates (petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	0 - 90
Distillates (petroleum), Solvent-refined Heavy Paraffinic	64741-88-4	0 - 90
White Mineral Oil (petroleum)	8042-47-5	0 - 90
Aluminum, (benzoato-o,o )hydroxy(octadecanoato-o,o )-	54326-11-3	2.5 - 10
Other components below reportable levels		2.5 - 10

**SECTION 3: HAZARDS IDENTIFICATION**

<b>Emergency overview</b>	Harmful in contact with eyes. Prolonged exposure may cause chronic effects.
<b>OSHA regulatory status</b>	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
<b>Potential health effects</b>	
<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Eyes</b>	Eye contact may result in corneal injury. Contact may irritate or burn eyes. Do not get this material in contact with eyes.
<b>Skin</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Avoid contact with the skin.
<b>Inhalation</b>	Avoid breathing dust/fume/gas/mist/vapors/spray.
<b>Ingestion</b>	Components of the product may be absorbed into the body by ingestion. Do not ingest.
<b>Target organs</b>	Eyes. RESPIRATORY SYSTEM. Skin.
<b>Chronic effects</b>	Conjunctiva. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Signs and symptoms</b>	Corneal damage. Conjunctivitis. Defatting of the skin. Skin irritation. Rash.
<b>Potential environmental effects</b>	May cause long-term adverse effects in the environment.



## SAFETY DATA SHEET

SDS DATE: 1/23/2012

---

### SECTION 4: FIRST AID MEASURES

---

**First aid procedures**

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

**Skin contact**

Wash off with warm water and soap. Get medical attention if irritation develops and persists.

**Inhalation**

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

**Ingestion**

Rinse mouth thoroughly. Do not induce vomiting. If ingestion of a large amount does occur, call a poison control center immediately. Never give liquid to an unconscious person.

**Notes to physician**

Symptoms may be delayed.

**General advice**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

---

### SECTION 5: FIRE-FIGHTING MEASURES

---

**Flammable properties**

Not flammable by OSHA criteria. Not combustible by OSHA criteria.

**Extinguishing media**

**Suitable extinguishing media**

Water fog. Foam. Dry powder. Carbon dioxide (CO2).

**Unsuitable extinguishing media**

Water. Do not use water jet as an extinguisher, as this will spread the fire.

**Protection of firefighters**

**Protective equipment and precautions for firefighters**

Wear suitable protective equipment.

**Fire fighting equipment/instructions**

Move containers from fire area if you can do so without risk.

**Hazardous combustion products**

Carbon monoxide and carbon dioxide.

---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**Personal precautions**

Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

**SECTION 6: ACCIDENTAL RELEASE MEASURES (Continued)****Methods for containment**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas.

**Methods for cleaning up**

Should not be released into the environment. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the MSDS.

**SECTION 7: HANDLING AND STORAGE****Handling**

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Avoid release to the environment.

**Storage**

Class IIIB Combustible Liquid.

Keep away from heat, sparks and open flame. Store in a well-ventilated place. Keep container tightly closed. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Use care in handling/storage.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Occupational exposure limits****ACGIH****Components**Distillates (petroleum),  
Hydrotreated Heavy  
Naphthenic (64742-52-5)**Type**

TWA

**Value**5 mg/m<sup>3</sup>**Form**

Inhalable Fraction.

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (Continued)****US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Aluminum, (benzoato-o,o )hydroxy(octadecanoato-o,o )- (54326-11-3)	TWA	1 mg/m3	Respirable fraction.
White Mineral Oil (petroleum) (8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
Distillates (petroleum), Hydrotreated Heavy Paraffinic (64742-54-7)	PEL	5 mg/m3	Mist.
Distillates (petroleum), Solvent-refined Heavy Paraffinic (64741-88-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
White Mineral Oil (petroleum) (8042-47-5)	PEL	5 mg/m3	Mist.

**Exposure guidelines** Occupational Exposure Limits are not relevant to the current physical form of the product.**Personal protective equipment**

<b>Eye / face protection</b>	Do not get in eyes. Chemical goggles are recommended. Eye wash fountain is recommended.
<b>Skin protection</b>	Wear appropriate chemical resistant clothing. Chemical resistant gloves.
<b>Respiratory protection</b>	No personal respiratory protective equipment normally required.
<b>General hygiene considerations</b>	Do not get in eyes. Avoid contact with skin. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Appearance</b>	Gel.
<b>Physical state</b>	Liquid.
<b>Form</b>	Grease
<b>Color</b>	Blue.
<b>Odor</b>	Mild.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Vapor pressure</b>	0 hPa estimated
<b>Density</b>	890 kg/m <sup>3</sup>
<b>Vapor density</b>	Not available.
<b>Boiling point</b>	680 °F (360 °C) estimated
<b>Melting point/Freezing point</b>	Not available.
<b>Solubility (water)</b>	Negligible
<b>Solubility (other)</b>	Oil
<b>Specific gravity</b>	0.89
<b>Relative density</b>	Not available.
<b>Flash point</b>	417.2 °F (214 °C) Pensky-Martens Closed Cup
<b>Flammability limits in air, upper, % by volume</b>	Not available.
<b>Flammability limits in air, lower, % by volume</b>	Not available.
<b>Auto-ignition temperature</b>	500 °F (260 °C) estimated
<b>VOC</b>	0.15 % estimated
<b>Viscosity</b>	180 cSt ASTM D445
<b>Percent volatile</b>	0.15 % estimated
<b>Other data</b>	
<b>Flammability class</b>	Combustible IIIB estimated
<b>Flash point class</b>	Combustible IIIB
<b>Viscosity temperature</b>	104 °F (40 °C)

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

**SECTION 10: STABILITY AND REACTIVITY**

<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Not available.
<b>Hazardous decomposition products</b>	Toxic gas. At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

**SECTION 11: TOXICOLOGICAL INFORMATION****Toxicological data****Product****Test Results**

Triple Guard Grease (Mixture)

Acute Dermal LD50 Rabbit: 52439.03 g/kg estimated  
Acute Oral LD50 Rat: 30333.33 g/kg estimated  
Acute Other LD50 Rat: 4634.15 mg/kg estimated**Local effects**

Components of the product may be absorbed into the body through the skin. Contact may irritate or burn eyes.

**Chronic effects**

Hazardous by OSHA criteria. Prolonged exposure may cause chronic effects.

**Carcinogenicity**

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**ACGIH Carcinogens**

Aluminum, (benzoato-o,o )hydroxy(octadecanoato-o,o )- ALUMINUM METAL AND INSOLUBLE COMPOUNDS, RESPIRABLE FRACTION (CAS 54326-11-3) A4 Not classifiable as a human carcinogen.

Distillates (petroleum), Hydrotreated Heavy Naphthenic MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 64742-52-5) A4 Not classifiable as a human carcinogen.

Distillates (petroleum), Solvent-refined Heavy Paraffinic MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 64741-88-4) A4 Not classifiable as a human carcinogen.

White Mineral Oil (petroleum) MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 8042-47-5) A4 Not classifiable as a human carcinogen.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

MINERAL OILS, HIGHLY-REFINED (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

**GENUINE PARTS**

BRP US Inc.  
10101 Science Drive  
Sturtevant, WI 53177

Contact: 262-884-5906

BRP Part No. 303719 775776  
508298 775777  
775615 775616  
775617 508181  
508299 508300  
509546 775780  
460794 460885  
765734 765736  
765737

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**Ecotoxicological data****Product****Test Results**

Triple Guard Grease (Mixture)

EC50 Daphnia: 22291.67 mg/l 48 hours estimated  
LC50 Fish: 43865.43 mg/l 96 hours estimated

\* Estimates for product may be based on additional component data not shown.

**Ecotoxicity**

Contains a substance which causes risk of hazardous effects to the environment.

**Environmental effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

**Persistence and  
degradability**

Not available.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**DOT**

Not regulated as dangerous goods.

**IATA**

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

---

**SAFETY DATA SHEET**

SDS DATE: 1/23/2012

---

**SECTION 15: REGULATORY INFORMATION**

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
One or more components are not listed on TSCA.

**CERCLA (Superfund) reportable quantity**  
None

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

**Section 302 extremely hazardous substance** No

**Section 311 hazardous chemical** Yes

**Clean Water Act (CWA)** Hazardous substance

**State regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004 Carcinogenic.

**US - New Jersey RTK - Substances: Listed substance**

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) Listed.

Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Listed.

Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4) Listed.

**US - Pennsylvania RTK - Hazardous Substances: Listed substance**

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) Listed.

Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Listed.

White Mineral Oil (petroleum) (CAS 8042-47-5) Listed.

---



**EVINRUDE  
Johnson**



**GENUINE PARTS**

BRP US Inc.  
10101 Science Drive  
Sturtevant, WI 53177

Contact: 262-884-5906

**BRP Part No.** 303719 775776  
508298 775777  
775615 775616  
775617 508181  
508299 508300  
509546 775780  
460794 460885  
765734 765736  
765737

## SAFETY DATA SHEET

SDS DATE: 1/23/2012

---

### SECTION 16: OTHER INFORMATION

---

#### Further information

HMIS® is a registered trade and service mark of the NPCA.

#### HMIS® ratings

Health: 1\*  
Flammability: 1  
Physical hazard: 0

#### NFPA ratings

Health: 1  
Flammability: 1  
Instability: 0

#### Disclaimer

Bel-Ray Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

#### Issue date

01-23-2012

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Alternate Trade Names