

Defender FRB400



1. Reinforced end-cone caps
2. Lateral storage pockets (2)
3. Reinforced rubbing strake
4. Air valves with overpressure valves
5. Anti-slip airfloor
6. Thrust board to stiffen air floor
7. Paddling saddles (4)
8. Bow D-rings for towing bridle (3)
9. Bow equipment storage bag
10. Port / starboard / stern reflective tape for night ops
11. Lifting Handles (6)
12. Exterior life line
13. Aluminum paddles with handles (4)
14. Re-righting rope in marked pouch
15. Manoeuvring line D-rings w/ wear patches (6)
16. Interior life line
17. Lacing cuff
18. Emergency anchor
19. Quick draining elephant trunks (2)
20. Outboard motor transom pad / plate
21. Reinforced transom bottom
22. Towing / lifting U-Bolts on transom (2)
23. Additional security eyes on transom (2)
24. Emergency diver's knife

FRB-400 Specifications

- Length – 4m / 13'1"
- Beam – 1m78 / 70"
- Tube Diameter – 46 cm / 18"
- Weight – 84 kg / 185 lbs
- Air Chambers – 7
- Material – European DuraTex 1450 g/m2 PVC from Mehler Technologies
- Carrying capacity – 7 persons / 630 kg / 1386 lbs
- Max. Engine 30 hp (22 kW)
- Design Category C (RCD 94/25/EC)

Shipping Information

- Shipping weight 94.5 kg / 208 lbs
- Shipping size – 130cm x 76cm x 45cm = .445 m3 (51" x 30" x 18" = 15.7 ft.3)

All Susceptible Areas Reinforced to Resist Damage

- Double wide heavy duty rubstrake
- Extra reinforcement on bottom of tubes and keel
- Protective non-skid on deck
- Wrapped transom with no exposed wood
- Anti-slip paddling saddles on tube tops
- Anti-chafe patches to protect boat from maneuvering lines

Additional standard equipment

- Carrying bag
- Inflation pump
- Repair kit

Defender[®]
Marine Outfitters of Choice Since 1938