

Model 729494 Bulb Replacement Kit for Guest 503 series Spot/Flood Light

Parts included

- (1) 55 watt/100 watt halogen bulb
- (1) Replacement bezel gasket
- (4) black replacement sealing washers

Tools required

- Pliers
- Phillips-head screw driver

Caution

- 1. Do not replace the bulb until it has cooled.
- 2. Do not touch the glass portion of the bulb or the shiny portion of the reflector with bare fingers.
- 3. Do not over-tighten screws during re-assembly.
- 4. Do not look directly at this bulb while it is lit.

Step 1

1. Point the head of the spotlight UP.
2. Turn the 12 volt power supply to the light OFF.

Step 2

Remove and keep the 4 phillips-head screws on the face of the light.

Step 3

1. Carefully remove the bezel, lens and reflector.
2. Gently un-plug the 3 wires from the bulb. Note their locations.

Step 4

1. Loosen the 2 screws holding the bulb into the reflector.
2. Gently remove the old bulb and discard.

Step 5

1. Locate the 2 small metal tabs on the new bulb.
2. Use pliers to bend them down flat.

Step 6

1. Insert the new bulb into the reflector.
2. Gently tighten the 2 screws that hold the bulb into the reflector.

Step 7

1. Gently re-connect the 3 wires to the new bulb.

Step 8

Remove the old gasket from the bezel and replace it with the new gasket. (included).

Step 9

Re-assemble the parts as shown using the 4 original screws and the 4 new black sealing washers (included).