

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name : Talon  
 Product form : liquid  
 Other means of identification : 6045 Black, 6042 Blue, 6041 Red, 6030 Dark Blue, 6043 Green  
*\*All colors are not available in all states*

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Antifouling

**1.3. Details of the supplier of the safety data sheet**

New Nautical Coatings, Inc.  
 Sea Hawk Premium Yacht Finishes  
 14805 49th Street North  
 Clearwater, FL 33762  
 USA Only: 1-800-528-0997  
 International: (727) 523-8053

**1.4. Emergency telephone numbers**

Emergency number : CHEMTREC day or night inside USA & Canada  
 1-800-424-9300  
 : CHEMTREC day or night outside USA & Canada  
 +1-703-741-5970  
 : Poison Control Center  
 1-800-222-1222

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (GHS-US)**

Flam. Liq. 3 H226  
 Acute Tox. 4 H302  
 Asp. Tox. 1 H304  
 Aquatic Chronic 1 H410  
 Aquatic Acute 1 H400  
 Skin Sens. 1 H317  
 Carc. 1A H350

*Contains 9.5% ingredients of unknown oral toxicity.*

**2.2. Label elements**

**GHS-US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H304 - May be fatal if swallowed and enters airways  
 H302 - Harmful if swallowed  
 H317 - May cause an allergic skin reaction  
 H350 - May cause cancer  
 H400 - Very toxic to aquatic life  
 H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment  
 P242 - Use only non-sparking tools  
 P243 - Take precautionary measures against static discharge  
 P261 - Avoid breathing fumes or mist.  
 P264 - Wash face, hands and forarms thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product  
 P272 - Contaminated work clothing must not be allowed out of the workplace  
 P273 - Avoid release to the environment  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection  
 P301+P310 - IF SWALLOWED: Immediately call a doctor.  
 P301+P312 - If swallowed: Call a doctor if you feel unwell  
 P302+P352 - If on skin: Wash with plenty of water.  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P321 - Specific treatment (see first aid instructions on this label)  
 P330 - Rinse mouth  
 P331 - Do NOT induce vomiting  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
 P362+P364 - Take off contaminated clothing and wash it before reuse  
 P370+P378 - In case of fire: Use water to extinguish  
 P391 - Collect spillage  
 P403+P235 - Store in a well-ventilated place. Keep cool  
 P405 - Store locked up  
 P501 - Dispose of contents/container to licenced waste handling facility.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Substance type:

: Multi-constituent

| Name  | Product identifier  | %        |
|---|---------------------|----------|
| Cupric oxide  | (CAS No) 1317-38-0  | 1-5      |
| Solvent naphtha(petroleum), light aromatic          | (CAS No) 64742-95-6 | 10-30    |
| Ethylbenzene  | (CAS No) 100-41-4   | 0.01 - 1 |
| Zinc oxide  | (CAS No) 1314-13-2  | 5-10     |
| Cuprous oxide                                       | (CAS No) 1317-39-1  | 30-45    |
| Cumene  | (CAS No) 98-82-8    | 0.1-1    |
| Pseudocumene  | (CAS No) 95-63-6    | 5-10     |
| C18-28 Long Chain Chlorinated Paraffins             | (CAS No) 63449-39-8 | 0.1-1    |
| Reaction product of epichlorohydrin and bisphenol A | (CAS No) 25085-99-8 | 0.1-1    |
| Crystalline silica (quartz)                         | (CAS No) 14808-60-7 | 0.1-1    |

Full text of H-phases: see section 16

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get immediate medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause nose and throat irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. May cause allergic skin reaction.
- Symptoms/injuries after eye contact : May cause eye irritation. Avoid contact with eyes.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause abdominal pain, nausea, vomiting or drowsiness.
- Chronic symptoms : Possible cancer hazard. Contains ingredients which may cause cancer based on animal data.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Water spray.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapor. May produce carbon oxides under fire conditions.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus and protective suit (see item 8).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Wear approved supplied-air respirator, in case of emergency.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

### 6.4. Reference to other sections

No additional information available

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Use appropriate personal protection equipment (PPE).

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

Storage temperature : < 38 °C (100°F)

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure

|  |   |
|--|---|
| <b>Ethylbenzene (100-41-4)</b>                                       |   |
| ACGIH TWA (ppm)  | 20 ppm  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                                  | 435 mg/m <sup>3</sup>   |
| OSHA PEL (TWA) (ppm)   | 100 ppm   |
| OSHA PEL (STEL) (mg/m <sup>3</sup> )                                 | 545 mg/m <sup>3</sup>   |
| OSHA PEL (STEL) (ppm)  | 125 ppm   |
| <b>Zinc oxide (1314-13-2)</b>  |   |
| ACGIH TWA (mg/m <sup>3</sup> )                                       | 2 mg/m <sup>3</sup>   |
| ACGIH STEL (mg/m <sup>3</sup> )                                      | 10 mg/m <sup>3</sup>  |
| <b>Cuprous oxide (1317-38-0)</b>                                     |   |
| ACGIH TWA (ppm)  | No Established Limit  |
| ACGIH STEL (ppm)   | No Established Limit  |
| <b>Cumene (98-82-8)</b>  |   |
| ACGIH TWA (ppm)  | 50 ppm  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                                  | 245 mg/m <sup>3</sup>   |
| OSHA PEL (TWA) (ppm)   | 50 ppm  |
| <b>Silica: Crystalline, quartz (14808-60-7)</b>                      |   |
| ACGIH TWA (mg/m <sup>3</sup> )                                       | 0.025 mg/m <sup>3</sup> (respirable fraction)   |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                                  | (10)/(%SiO <sub>2</sub> + 2) total dust; (10)/(%SiO <sub>2</sub> + 2) respirable fraction |
| OSHA PEL (TWA) (ppm)   | (250)/(%SiO <sub>2</sub> + 5) respirable fraction   |
| <b>Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)</b> |   |
| Remark (ACGIH)   | OELs not established  |
| Remark (OSHA)  | OELs not established  |

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. Handle with good industrial hygiene and safety.  
 Personal protective equipment : Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                          |  |
|--------------------------|--|
| Eye protection           | : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles. |
| Skin and body protection | : Wear long sleeves.Handle with gloves   |
| Respiratory protection   | : An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.          |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| Physical state                              | : Liquid  |
| Appearance                                  | : liquid.   |
| Color                                       | : Black, Blue, Red, Dark Blue, Green <i>*All colors are not available in all states</i>   |
| Odor  | : Aromatic odour.   |
| Odor Threshold                              | : No data available   |
| pH  | : No data available   |
| Relative evaporation rate (butyl acetate=1) | : Not Measured  |
| Relative evaporation rate (ether=1)         | : Not Measured  |
| Melting point                               | : No data available   |
| Freezing point                              | : No data available   |
| Boiling point                               | : Not Measured  |
| Flash point                                 | : Black = 100°F (38°C)<br>Blue = 100°F (38°C)<br>Red = 100°F (38°C)<br>Dark Blue = 100°F (38°C)<br>Green = 100°F (38°C)<br><i>*All colors are not available in all states</i>   |
| Self ignition temperature                   | : Na data available   |
| Decomposition temperature                   | : No data available   |
| Flammability (solid, gas)                   | : No data available   |
| Vapor pressure                              | : Not Measured  |
| Relative vapor density at 20 °C             | : Heavier than air  |
| Relative density                            | : Black = 1.86 g/ml at 77°F (25°C)<br>Blue = 1.87 g/ml at 77°F (25°C)<br>Red = 1.92 g/ml at 77°F (25°C)<br>Dark Blue = 1.89 g/ml at 77°F (25°C)<br>Green = 1.85 g/ml at 77°F (25°C)<br><i>*All colors are not available in all states</i> |
| Solubility                                  | : Water: None   |
| Log Pow                                     | : No data available   |
| Log Kow                                     | : No data available   |
| Viscosity, kinematic                        | : No data available   |
| Viscosity, dynamic                          | : No data available   |
| Explosive properties                        | : No data available   |
| Oxidizing properties                        | : No data available   |
| Explosive limits                            | : No data available   |

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion:CO and CO<sub>2</sub> are formed.Reacts violently with strong oxidizers:increased risk of fire/explosion.reacts with some acids.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremes of temperature and direct sunlight.

### 10.5. Incompatible materials

Avoid contact with : Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

| <b>Ethylbenzene (100-41-4)</b> |                             |
|--------------------------------|-----------------------------|
| LD50 oral rat                  | 3500 mg/kg                  |
| LD50 dermal rabbit             | 15354 mg/kg                 |
| LC50 inhalation rat (mg/l)     | 17.2 mg/l/4h                |
| ATE (oral)                     | 3500.000 mg/kg body weight  |
| ATE (dermal)                   | 15354.000 mg/kg body weight |
| ATE (dust, mist)               | 1.500 mg/l/4h               |

| <b>Cuprous oxide (1317-39-1)</b> |                           |
|----------------------------------|---------------------------|
| LD50 oral rat                    | 470 mg/kg Category 4      |
| LD50 skin rabbit                 | 2000.00 mg/kg Category 4  |
| LD50 inhalation vapor rat        | No data available         |
| LD50 inhalation dust/mist rat    | 50.00 mg/l/4h Category NA |

| <b>Zinc oxide (1314-13-2)</b>   |                         |
|---------------------------------|-------------------------|
| LD50 oral rat                   | 5000 mg/kg Category 5   |
| LD50 skin rabbit                | No data available       |
| LD50 inhalation vapor rat       | No data available       |
| LD50 inhalation dust/mist mouse | 2.50 mg/l/4h Category 4 |

| <b>Cumene (98-82-8)</b>                         |                |
|---|----------------|
| LD50 oral rat                                   | 1400 mg/kg     |
| LD50 dermal rabbit                              | 12300 µg/kg    |
| LC50 inhalation rat (ppm)                       | > 3577 ppm 6 h |
| <b>Silica: Crystalline, quartz (14808-60-7)</b> |                |
| LD50 oral rat                                   | 500 mg/kg      |

Carcinogenicity data:

| <b>Ethylbenzene (100-41-4)</b>                                       |                                      |
|--|--------------------------------------|
| IARC group   | 2B - Possibly carcinogenic to humans |
| <b>Cumene (98-82-8)</b>  |                                      |
| IARC group   | 2B - Possibly carcinogenic to humans |
| <b>Toluene (108-88-3)</b>  |                                      |
| IARC group   | 3 - Not classifiable                 |
| <b>Silica: Crystalline, quartz (14808-60-7)</b>                      |                                      |
| IARC group   | 1 - Carcinogenic to humans           |
| <b>Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)</b> |                                      |
| IARC group   | 2B - Possibly carcinogenic to humans |

|                                   |  |
|-----------------------------------|--|
| Skin corrosion/irritation         | : Not classified                       |
| Serious eye damage/irritation     | : Not Applicable, Not classified       |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity            | : Not Applicable, Not classified       |
| Carcinogenicity                   | : May cause cancer                     |
| Acute Toxicity(Mouth)             | Harmful if swallowed.                  |
| Acute Toxicity( skin)             | Not Classified                         |

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| Reproductive toxicity                              | : Not Applicable, Not classified               |
| Specific target organ toxicity (single exposure)   | : Not Applicable, Not classified               |
| Specific target organ toxicity (repeated exposure) | : Not Applicable, Not classified               |
| Aspiration hazard                                  | : May be fatal if swallowed and enters airways |

### SECTION 12: Ecological information

#### 12.1. Toxicity

| Cuprous oxide (1317-39-1) |   |
|---------------------------|---|
| LC50 fishes l             | 0.075 mg/l (96 h; danio rerio)                    |
| EC50 daphnia l            | 0.042 mg/l (48 h; Daphnia similis)                |
| Threshold limit algae l   | 0.03 mg/l (96 h; Pseudokirchneriella subcapitata) |

  

| Zinc oxide (1314-13-2)  |   |
|-------------------------|---|
| LC50 fishes l           | 1.10 mg/l (96 h; Oncorhynchus mykiss)               |
| EC50 daphnia l          | 0.098 mg/l (48 h; Daphnia magna)                    |
| Threshold limit algae l | 0.042 mg/l (72 h; Pseudokirchneriella subcapitata ) |

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

#### 12.5. Other adverse effects

PBT/vPvB assessment not available as chemical safety assessment not required/ not conducted

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

UN-No.(DOT) : 1263  
DOT NA no. : UN1263

#### 14.2. UN proper shipping name

DOT Proper Shipping Name : paint

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III-Minor Danger

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Additional information

#### Transportation by land(ADR)

Transport document description : UN 1263 ,PAINT,3,III,(D/E)

Packaging group (ADR) : III  
Class (ADR) : 3- Flammable liquid  
State during Transport(ADR-RID) : As liquid

Hazard identification number (Kemler No.) : 30

Classification code( ADR) : F1

Tunnel restriction code : D/E  
Danger labels (ADR) : 3 - Flammable liquid



#### Transport by sea

UN-No. (IMDG) : 1263  
Packaging Group : III  
  
Class (IMDG) : 3- Flammable liquid  
EmS-No.(1) : F-E  
EmS-No.(2) : S-E  
Marine Pollutant : Yes

#### Air transport

UN-No. (IATA) : 1263.  
  
Class (IATA) : 3- Flammable liquid  
  
Packaging group (IATA) : III-Minor Danger

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) :  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) :

Other information : No supplementary information available.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Cumene (98-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on United States SARA Section 313



# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |   |
|---|---|
| <b>Cumene (98-82-8)</b>   |   |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 5000 lb   |
| SARA Section 313 - Emission Reporting   | 1 %   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on United States SARA Section 313 |   |
| SARA Section 313 - Emission Reporting   | 1 %   |
| <b>Ethylbenzene (100-41-4)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on United States SARA Section 313 |   |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 1000 lb   |
| SARA Section 313 - Emission Reporting   | 0.1 %   |
| <b>Toluene (108-88-3)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on United States SARA Section 313 |   |
| <b>Benzene (71-43-2)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on United States SARA Section 313 |   |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 10 lb (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule) |
| SARA Section 313 - Emission Reporting   | 0.1 %   |

### 15.2. International regulations

#### CANADA

No additional information available

#### 15.2.2. National regulations

|   |
|---|
| <b>Ethylbenzene (100-41-4)</b>  |
| Listed on IARC (International Agency for Research on Cancer)<br>Listed on Inventory of Existing Chemical Substances (IECSC)<br>Listed on the AICS (the Australian Inventory of Chemical Substances)<br>Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.<br>Listed on the Korean ECL (Existing Chemical List) inventory. |
| <b>Cuprous oxide (1317-39-1)</b>  |
| Listed on the AICS (the Australian Inventory of Chemical Substances)<br>Listed on Inventory of Existing Chemical Substances (IECSC)<br>Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.<br>Listed on KECI (Chemical Inventory of Korea)   |

### 15.3. US State regulations

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| <b>Ethylbenzene (100-41-4)</b>                        |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes   | No  | No  | No  |                                   |
| <b>Cumene (98-82-8)</b>                               |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes   | No  | No  | No  |                                   |
| <b>Toluene (108-88-3)</b>                             |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No  | Yes   | No  | No  |                                   |

# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |   |   |                                   |
|--|---|---|---|-----------------------------------|
| <b>Benzene (71-43-2)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List  | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes  | Yes   | No  | Yes   |                                   |
| <b>Silica: Crystalline, quartz (14808-60-7)</b>  |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List  | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes  | No  | No  | No  |                                   |
| <b>Ethylbenzene (100-41-4)</b>   |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Massachusetts - Right To Know List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List   |   |   |   |                                   |
| <b>Cumene (98-82-8)</b>  |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List   |   |   |   |                                   |
| <b>Toluene (108-88-3)</b>  |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List                           |   |   |   |                                   |
| <b>Benzene (71-43-2)</b>   |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |   |   |   |                                   |
| <b>Silica: Crystalline, quartz (14808-60-7)</b>  |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List<br>U.S. - Massachusetts - Right To Know List  |   |   |   |                                   |
| <b>Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)</b>   |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List  |   |   |   |                                   |
| <b>Pseudocumene (95-63-6)</b>  |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List<br>U.S. - Massachusetts - Right To Know List  |   |   |   |                                   |
| <b>Cuprous oxide (1317-39-1)</b>   |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List   |   |   |   |                                   |
| <b>Zinc oxide (1314-13-2)</b>  |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List   |   |   |   |                                   |

### SECTION 16: Other information

- Indication of changes : Revision 3.0 – 12/19/2016 - Updated.
- Other information : Mario Garneau, edited by EKW
- NFPA health hazard : 2-intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given



# Talon

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

NFPA fire hazard : 3 – Liquids and solids that can be ignited under almost all ambient conditions

NFPA reactivity : 0-Normally stable, even under fire exposure conditions, and are not reactive with water.

### HMIS III Rating

Health : 2\*

Flammability : 3

Physical hazard : 0

Personal Protection : H

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material. No warranty, express or implied, is made and New Nautical Coatings, Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.