



TRIDENT MARINE®

A2 FUEL FILL & DIESEL TRANSFER LINE



329 Series

Trident A2 Corrugated Fuel Fill Hose for gasoline fill hose (including ethanol blends) and diesel (including bio diesel blends). The #327 series exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840, & USCG Type A2; and is NMMA Type Accepted, CE certified and Lloyds Registry Type Approved. This hose is built with the best fuel, fire and age resistant formulation. Provides extraordinary resistance to aging, fire, heat, cold, and the ozone. Also provides extraordinary flexibility and bend radius.

Specifications

Construction:

Tube: NBR

Cover: NBR/EPDM Blend

Reinforcement: High Tenacity Polyester 2 spiral, Spring Steel Helix

Temperature Range: -4°F to 212°F (-20°C to 100°C)

Lengths: 12.5' (3.81 m) **Length,** 12.5' (3.81 m) **Boxed,** 25' (7.62 m) **Boxed,** 50' (15.24 m) **Coil**

Part Number	ID		OD		Wall		Working Pressure		Bend Radius	
	in.	mm.	in.	mm.	in.	mm.	psi	mpa	in.	mm.
329-1120	1-1/2	38	2.0	51	0.25	6.4	60	0.41	3.5	89
329-2000	2	50.8	2.48	63.5	0.25	6.4	50	0.345	5.0	127

TRIDENT RUBBER INC.
585 PLUM RUN ROAD
CANONSBURG PA, 15317

1-800-414-2628

WWW.TRIDENTMARINE.COM